

Link do produktu: <https://mig.bytom.pl/dgs-1210-28p-24-gbit-poe-smart-4xsfp-p-15947.html>

DGS-1210-28P 24 Gbit POE Smart, 4xSFP



Cena brutto	2 082,00 zł
Cena netto	1 692,68 zł
Dostępność	Aktualnie niedostępny
Czas wysyłki	24 godziny
Numer katalogowy	1NUDLISS28DGS000
Kod producenta	DGS-1210-28P
Kod EAN	790069373053

Opis produktu

Architektura sieci (switche):
Bezpieczeństwo:

Bufor pamięci (switche):
Funkcje L2:

Funkcje L3:

Klasa przełącznika:
Liczba grup VLAN (tylko mng i smart):
Liczba portów 10/100 Mbps:
Liczba portów 10/100/1000 Mbps:
Liczba portów 10Gb:
Liczba portów COMBO:
Liczba portów PoE (PoE + PoE+):
Liczba portów PoE+:
Liczba portów QSFP+:
Liczba portów SFP:
Liczba portów SFP+:
Obsługa ramek Jumbo:
Pobór mocy:
Prędkość przekazywania (Mpps):

GigabitEthernet
- Broadcast/Multicast/Unicast Storm Control - D-Link Safeguard Engine - DHCP Server Screening - IP-MAC-Port Binding (Smart Binding) - Supports 512 address binding entries - ARP Inspection - ARP + IP Inspection - Supports DHCP Snooping - 802.1X Port-based Access Control - ARP Spoofing Prevention - Max. 64 entries - Traffic Segmentation - SSH v2 - SSL - Supports v1/v2/v3 - Port Security - Supports up to 64 MAC addresses per port - Duplicate address detection
1.5
- MAC Address Table - 16K entries - IGMP Snooping - IGMP v1/v2 Snooping - Supports 256 IGMP groups - Supports at least 64 static multicast addresses - IGMP per VLAN - Supports IGMP Snooping Querier - Loopback Detection - 802.3ad Link Aggregation: - DGS-1210 28/28P: Maximum of 14 groups/8 ports per group - DGS-1210 52/52MP/52P: Maximum of 26 groups/8 ports per group - DGS-1210 -10/10P: Maximum of 5 groups/8 ports per group - LLDP -LLDP-MED - Jumbo Frame - Up to 9,216 bytes - Spanning Tree Protocol - 802.1D STP - 802.1w RSTP - Flow Control - 802.3x Flow Control - HOL Blocking Prevention - Port Mirroring - One-to-One - Many-to-One - Supports Mirroring for Tx/Rx/Both - Multicast Filtering - Forwards all unregistered groups - Filters all unregistered groups - Configurable MDI/MDIX - MLD snooping v1/v2 (256 groups)
- IP Interface - Supports 1 interface - IPv6 Neighbor Discovery (ND)
SMART
256
Brak
24
Brak
Brak
24
Brak
Brak
4
Brak
Tak
251.3
41.7

Przepustowość (switche Gbps):	56
QoS:	- 802.1p Quality of Service - 8 queues per port - Queue Handling - Strict - Weighted Round Robin (WRR) - Bandwidth Control - Port-based (Ingress/Egress, min granularity 10/100/1000 is 64 Kbps) - QoS based on: - 802.1p Priority Queues - DSCP - ToS - IPv6 Traffic Class - TCP/UDP port
Rozmiar ramki Jumbo:	9
Rozmiar tablicy adresów MAC:	16000
Tryb przekazywania:	Store-and-forward
Typ obudowy:	Rack (Switch/UPS)
VLAN:	- 802.1Q - VLAN Group - Max. 256 static VLAN groups - Configurable VID from 1 - 4094 - Asymmetric VLAN - Auto Voice VLAN - Max. 10 user-defined OUI - Max. 8 default OUI - Auto Surveillance VLAN
Waga:	2.54
Warstwa przełączania (switche):	L2
Wentylator (switche):	Tak
Wymiary:	440 x 210 x 44 mm
Zarządzanie, monitorowanie, konfiguracja:	- Web-based GUI - D-Link Network Assistant Utility - Compact CLI - Telnet Server - TFTP Client - Configurable MDI/MDIX - SNMP - Supports v1/v2c/v3 - SNMP Trap - Backup/Upgrade firmware - Smart Wizard - Upload/Download Configuration file - System Log - Max. 500 log entries - BootP/DHCP Client - SNTP - ICMP v6 - IPv4/v6 Dual Stack - DHCP Auto Configuration - Time Setting - SNTP - RMONv1 - Trusted Host
Zasilacz (switche):	Wewnętrzny
Zasilanie:	10 to 240 VAC, 50/60HZ
Zastosowanie (switche):	Średnie i duże firmy (powyżej 16 portów)