

Link do produktu: <https://mig.bytom.pl/dgs-1510-28p-poe-switch-24xgb-2sfp-2xsfp-p-15948.html>



DGS-1510-28P PoE Switch 24xGb+2SFP+2xSFP+

Cena brutto	3 351,00 zł
Cena netto	2 724,39 zł
Dostępność	Aktualnie niedostępny
Czas wysyłki	24 godziny
Numer katalogowy	1NUDLISS28DGS002
Kod producenta	DGS-1510-28P
Kod EAN	790069399473

Opis produktu

Architektura sieci (switche):
Bezpieczeństwo:

Bufor pakietów:
Funkcje L2:

Funkcje L3:

Klasa przełącznika:
Liczba grup VLAN (tylko mng i smart):
Liczba portów 10/100 Mbps:
Liczba portów 10/100/1000 Mbps:
Liczba portów COMBO:
Liczba portów PoE (PoE + PoE+):
Liczba portów PoE+:
Liczba portów QSFP+:
Liczba portów SFP:

GigabitEthernet
- Port Security - Supports up to 128 MAC addresses per port - Broadcast/Multicast/Unicast Storm Control - Dynamic ARP Inspection - Static MAC - D-Link Safeguard Engine - DHCP Server Screening - ARP Spoofing Prevention - Max. 64 entries - SSH - Supports v02 - Supports IPv4/IPv6 - SSL - Supports v1/v2/v3 - Supports IPv4/IPv6 - Traffic Segmentation - IP-MAC-Port Binding - DHCP snooping - IP Source Guard - Dynamic ARP inspection - DHCPv6 Guard - RA Guard - IPv6 Snooping - IPv6 source guard - DoS Attack Prevention
1.5
- MAC Address Table: 16K - Flow Control - 802.3x Flow Control - HOL Blocking Prevention - Jumbo Frame up to 9000 Bytes - IGMP Snooping - IGMP v1/v2 Snooping - IGMP v3 awareness - Supports 512 IGMP groups - Supports 128 static multicast addresses - IGMP per VLAN - Supports IGMP Snooping Querier - Host-based IGMP Snooping Fast Leave - MLD Snooping - Supports MLD v1/v2 awareness - Supports 512 groups - Supports 128 Static Multicast Addresses - Per VLAN MLD Snooping - Host-Based MLD Fast Leave - MLD Snooping Querier - Spanning Tree Protocol - 802.1D STP - 802.1w RSTP - 802.1s MSTP - Loopback Detection -802.3ad Link Aggregation - Max. 32 groups per device/8 ports per group - Port Mirroring - Support 4 mirroring groups - One-to-One, Many-to-One - Supports Mirroring for Tx/Rx/Both - Multicast Filtering - Forwards all unregistered groups - Filters all unregistered groups - LLDP, LLDP-MED - ERPS (Ethernet Ring Protection Switching)
- ARP - 256 Static ARP - Supports Gratuitous ARP - IPv6 Neighbour Discovery (ND) - 16 IP interfaces- Default Routing - Static Routing - 64 IPv4 Static Route Entries - 32 IPv6 Static Route Entries
SMART
256
Brak
24
Brak
24
Brak
Brak
2

Liczba portów SFP+:	2
Obsługa ramek Jumbo:	Tak
Pobór mocy:	238.7
Port konsoli:	Tak
Prędkość przekazywania (Mpps):	68.45
Przepustowość (switche Gbps):	92
QoS:	- 802.1p Quality of Service - Queue Handling - Strict - Weighted Round Robin (WRR) - 8 queues per port - Bandwidth Control - Port-based (Ingress/Egress, min. granularity for 10/100/1000Base-T ports is 64 Kb/s) - CoS based on - 802.1p priority - VLAN - MAC address - Ether type - IP address - DSCP - Protocol type - TCP/UDP port number - DSCP of IPv6 Traffic Class - IPv6 flow label
Rozmiar ramki Jumbo:	9
Rozmiar tablicy adresów MAC:	16000
Typ obudowy:	Rack (Switch/UPS)
VLAN:	- 802.1Q Tagged VLAN - 4K VLAN Groups - Configurable VID: 0~4094 - Asymmetric VLAN - Auto Voice VLAN - Auto Surveillance VLAN
Waga:	2.54
Warstwa przełączania (switch):	L2
Wentylator (switch):	Tak
Wymiary:	440 x 250 x 44 mm
Zarządzanie, monitorowanie, konfiguracja:	- CLI - Telnet Server - TFTP Client - IPv6 Neighbor Discovery - Configurable MDI/MDIX - SNMP - Supports v1, v2c, v3 - SNMP Trap - System Log - Max. 10,000 log entries - DHCP Client - D-Link Network Assistant support - SNTP - ICMPv6 - IPv4/v6 Dual Stack - DHCP Auto Configuration - RMON v1- sFow- NTP (RFC5905)
Zasilacz (switch):	Wewnętrzny
Zasilanie:	100 to 240 VAC, 50 to 60Hz
Zastosowanie (switch):	Średnie i duże firmy (powyżej 16 portów)