

Link do produktu: <https://mig.bytom.pl/przelacznik-zaradzalny-dgs-3630-28tc-si-24xge-4xsfp-4xsfp-p-15981.html>

Przełacznik zarządzalny DGS-3630-28TC/SI 24xGE 4xSFP 4xSFP+



Cena brutto	8 368,00 zł
Cena netto	6 803,25 zł
Dostępność	Aktualnie niedostępny
Czas wysyłki	24 godziny
Numer katalogowy	1NUDLISZ24000011
Kod producenta	DGS-3630-28TC/SI
Kod EAN	790069425622

Opis produktu

Gigabitowe stakowalne zarządzalne przełączniki L3 Seria DGS3630.

Architektura sieci (switche):
Bezpieczeństwo:

Bufor pakietów:
Czas pracy pomiędzy awariami (MTBF):
Funkcje L2:

Funkcje L3:

Klasa przełącznika:
Liczba portów 10/100/1000 Mbps:
Liczba portów COMBO:
Liczba portów SFP+:
Możliwość łączenia w stos:
Obsługa ramek Jumbo:
Pobór mocy:
Port konsoli:
Prędkość przekazywania (Mpps):
Przepustowość (switche Gbps):

GigabitEthernet
Port Security Supports up to 12K MAC addresses per port/VLAN/system Broadcast/Multicast/Unicast Storm Control D-Link Safeguard Engine DHCP Server Screening Dynamic ARP Inspection IP Source Guard DHCP Snooping IPv6 Snooping Dynamic ARP Inspection (DAI) DHCPv6 Guard IPv6 Route Advertisement (RA) Guard IPv6 ND Inspection Duplicate Address Detection (DAD) ARP Spoofing Prevention Max. 64 entries L3 Control Packet Filtering Unicast Reverse Path Forwarding (URPF) Traffic Segmentation SSL Supports TLS 1.0/1.1/1.27 Supports IPv4/IPv6 access SSH Supports SSH v2 Supports IPv4/IPv6 access BPDU Attack Prevention DOS Attack Prevention NetBIOS/NetBEUI filtering
4
300190.46
MLD Snooping MLD v1/v2 Snooping Supports up to 4K MLD groups4 Host-based MLD Snooping Fast Leave Supports 64 static MLD groups MLD Snooping Querier Per VLAN MLD Snooping MLD Proxy Reporting IGMP Snooping IGMP v1/v2/v3 Supports up to 8K MLD groups4 Supports 64 static IGMP groups Per VLAN IGMP Snooping IGMP Snooping Querier Host-based IGMP Snooping Fast Leave PIM Snooping
IPv4 ARP/IPv6 ND: support up to 32K/16K4 512 Static ARP Gratuitous ARP IP Interface Supports 256 interfaces Loopback Interface Proxy ARP Support local ARP proxy IPv6 Tunneling Static ISATAP GRE 6to4 VRRP v2/v3 IP Helper
Zarządzalny
24
4
4
Tak
Tak
28.1
Tak
95.24
128

QoS:	802.1p 8 queues per port Queue Handling Strict Priority (SP) Weighted Round Robin (WRR) Strict + WRR Weighted Deficit Round Robin (WDRR) Congestion Control Weighted Random Early Detection (WRED) 802.1Qbb Priority-based Flow Control (PFC) for 10 GbE port Bandwidth Control Port-based (Ingress/Egress, min. granularity 8 Kb/s) Flow-based (Ingress/Egress, min. granularity 8 Kb/s) Per queue bandwidth control (min. granularity 8 Kb/s) Policy Map Remark 802.1p priority Remark IP precedence/DSCP Time based QoS CoS based on: Switch Port Inner/ outer 802.1p Priority Inner/ outer VID MAC address Ether Type IP address ToS/IP Preference DSCP Protocol Type TCP/UDP port IPv6 Traffic Class IPv6 Flow Label Three Color Marker trTCM srTCM
Rozmiar ramki Jumbo:	12
Rozmiar tablicy adresów MAC:	68000
Tryb przekazywania:	Store-and-forward
Typ obudowy:	Rack (Switch/UPS)
VLAN:	802.1Q 802.1v Protocol-based VLAN Double VLAN (Q-in-Q) Port-based Q-in-Q Selective Q-in-Q Port-based VLAN MAC-based VLAN Subnet-based VLAN Private VLAN VLAN Group Max. 4K VLAN groups Max. 4094 VIDs Multicast VLAN (ISM VLAN for IPv4/IPv6) Voice VLAN Auto Surveillance VLAN VLAN Trunking GVRP: Up to 4K dynamic VLANs Asymmetric VLAN
Waga:	3.74
Warstwa przełączania (switch):	L3
Wentylator (switch):	Tak
Wymiary:	441 x 259.8 x 44 mm
Zarządzanie, monitorowanie, konfiguracja:	NTPv3/v4 Precision Time Protocol (PTP) Web-based GUI Support IPv4/IPv6 access Support SSL (HTTPS) Command Line Interface (CLI) Telnet Server for IPv4/IPv6 access Telnet Client for IPv4/IPv6 SNMP Support v1/v2c/v3 Support IPv4/IPv6 access SNMP Trap TFTP Client for IPv4/IPv6 FTP Client for IPv4/IPv6 IPv4 SFTP Server RCP System Log for IPv4/IPv6 Syslog Server SMTP RMONv1 Supports 1,2,3,9 groups RMONv2 Supports ProbeConfig group Command Logging LLDP/LLDP-MED D-Link Discover Protocol (DDP) DHCP Client option 12 DHCP Auto-configuration DHCP Auto-image DHCP Relay option 60/61/62/18/37/125 DHCP/DHCPv6 Local Relay DHCP Server Support IPv4/IPv6 address assignment DHCPv6 Prefix Delegation (PD) Multiple Images/ Multiple Configurations DNS Relay for IPv4/IPv6 DNS Client for IPv4/IPv6 Debug Command Password Recovery/ Encryption Ping/ Traceroute for IPv4/IPv6 Microsoft Network Load Balancing (NLB) Switch Resource Management (SRM) sFlow D-Link License Management System (DLMS)
Zasilacz (switch):	Wewnętrzny
Zasilanie:	100 to 240 VAC 50/60 Hz
Zastosowanie (switch):	Średnie i duże firmy (powyżej 16 portów)