

Link do produktu: <https://mig.bytom.pl/switch-xgs4600-32f-24xsfp-4xgb-sfp-4x10gb-sfp-p-16608.html>

Switch XGS4600-32F 24xSFP 4xGb/SFP 4x10Gb SFP+



Cena brutto	9 734,00 zł
Cena netto	7 913,82 zł
Dostępność	Aktualnie niedostępny
Czas wysyłki	24 godziny
Numer katalogowy	1NUZYXSZ32000002
Kod producenta	XGS4600-32F-ZZ0102F
Kod EAN	4718937590575

Opis produktu

Architektura sieci (switche):
Bezpieczeństwo:

Bufor pakietów:
Klasa przełącznika:
Liczba portów 10/100 Mbps:
Liczba portów 10Gb:
Liczba portów COMBO:
Liczba portów PoE (PoE + PoE+):
Liczba portów PoE+:
Liczba portów QSFP+:
Liczba portów SFP:
Liczba portów SFP+:
Obsługiwane protokoły i standardy:

Pobór mocy:
Port konsoli:
Prędkość przekazywania (Mpps):
Przepustowość (switche Gbps):
QoS:

GigabitEthernet
- IEEE 802.1Q tag-based and port-based VLAN- GVRP automatic VLAN member registration- 1 K static VLANs and up to 4 K dynamic VLANs- Full range 4 K PVID support- Port-based VLAN and VLAN isolation- IP classification VLAN- VLAN counter- VLAN search- VLAN translation- VLAN MAC limit- Intrusion lock- MAC freeze- MAC search- MAC filtering- Port security- Limited MAC number per port- IP source guard- Loop guard- IP filtering- TCP/UDP socket filtering- BPDU transparency- IEEE 802.1X port-based authentication- Enhanced 802.1X compensation assignment over VLAN- TACACS+- Layer 2 protocol tunneling- Guest VLAN
4
Zarządzalny
Brak
4
4
Brak
Brak
Brak
24
4
- IEEE 802.3 10Base-T Ethernet- IEEE 802.3u 100Base-Tx Ethernet- IEEE 802.3ab 1000Base-T Ethernet- IEEE 802.3z 1000 Base-X- IEEE 802.3x flow control- IEEE 802.3az EEE support- IEEE 802.1p CoS support- IEEE 802.1D Spanning Tree Protocol (STP)- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)- IEEE 802.1Q VLAN tagging- IEEE 802.1X Port authentication- IEEE 802.3ad LACP aggregation
47
Tak
101.1
136
- Two Rate Three Color Marker (trTCM)- CIR/PIR bandwidth control- Port-based egress traffic shaping- Broadcast storm control- IEEE 802.1p with 8 priority queues per port- WFR, WRR, SPQ scheduling algorithms- DSCP/DSCP to 802.1p priority mapping- IGMP/IGMP snooping v1, v2, v3- IGMP throttling- IGMP snooping fast leave- IGMP snooping statistics- Multicast VLAN Registration (MVR)- Congestion control on all

Rozmiar tablicy adresów MAC:	ports- Selective Q-in-Q
Tryb przekazywania:	32000
Typ obudowy:	Store-and-forward
Waga:	Rack (Switch/UPS)
Warstwa przełączania (switche):	3.96
Wymiary:	L3
Zarządzanie, monitorowanie, konfiguracja:	441 x 270 x 44 mm
	- Zyxel iStacking™, up to 24 switches managed by a single IP address- Physical stacking up to 4 switches- Web-based management- Telnet- SSH- SNMP v1, v2c, v3- RS-232c local console- IP management: static IP or DHCP-assigned IP- Four RMON groups 1, 2, 3, 9 (history, statistics, alarms and events)- Port mirroring: ingress/egress/both port mirroring- IEEE 802.1AB LLDP- Transceiver DDMI information (including MIB)- sFlow
Zasilanie:	100 - 240 V AC, 50/60 Hz
Zastosowanie (switche):	Średnie i duże firmy (powyżej 16 portów)